




潍坊市永达玻璃钢有限公司
Weifang Yongda FRP Co., Ltd.
plasticfrp.com

品质卓越是永恒的主题
QUALITY EXCELLENCE IS THE ETERNAL THEME

永达玻璃钢 专业环保设备供应商
诚实守信 创新超越 以客为尊 互利双赢



Fiberglass Ventilation Ducts Frp Pipe Fiberglass Process Ducts

Our Product Introduction

Basic Information

- Place of Origin: ShanDong province, CHINA
- Brand Name: yongda
- Model Number: Customized
- Minimum Order Quantity: one meter, to be negotiated
- Price: \$5-10/meter USD 5-10 per meter, to be negotiated
- Packaging Details: nude packing or bundled TEU or FR TEU, to be negotiated
- Delivery Time: 15 days To be negotiated according order
- Supply Ability: 1000 meters per week



Product Specification

- Colour: Achieve Customized Quantity
- Length: 6m-12m
- Diameter: Advance Explanation
- Purpose: Gas Or Liquid
- Temperature: High Temperature Needs To Be Explained In Advance
- Medium: Need Detailed Explanation
- Highlight: **Fiberglass ventilation ducts,
Frp pipe ventilation ducts,
fiberglass process ducts**

for more products please visit us on plasticfrp.com

Product Description

Product Description:

Fiberglass tube props have the following main characteristics:

Corrosion resistance: Fiberglass tube props have excellent corrosion resistance, which can resist the erosion of various corrosive media such as acids, alkalis, salts, etc., especially suitable for industries such as chemical, pharmaceutical, printing and dyeing

Lightweight and high-strength: The specific gravity of fiberglass pipes is about $1.6-2.0\text{g/cm}^3$, which is only about 1/4 of ordinary steel, but it has high specific strength and fatigue resistance

Low fluid resistance: Its inner wall is smooth, with a low roughness coefficient, which can reduce fluid pressure loss along the way and improve conveying capacity

Easy installation: Due to its light weight, installation and maintenance are relatively easy, and no rust or anti-corrosion treatment is required, reducing installation and maintenance costs

Flexible design: can be customized according to specific usage situations, including winding angle, wall thickness, material, and connection method, etc

Good insulation performance: Fiberglass pipes are non-conductive and have excellent electrical insulation and thermal insulation properties, suitable for densely populated areas of power transmission and telecommunications lines

Environmental characteristics: Fiberglass pipes are made of non-metallic materials, with a rust free surface and no pollution to water quality. They are suitable for environments such as sewage treatment



Technical Parameters:

Attribute	Value
Product Name	Reinforced Fiberglass Pipe
Process	Filament Winding Method
Use	Water, Oil Treatment
Shape	Round
Diameter Range	DN50-2000mm

Support and Services:

1. 24-hour uninterrupted service, the hotline is always at your service! Our service hotline is 15069606988, and our factory provides free technical consulting services. If necessary, we can dispatch technical personnel to the site for investigation.
2. Any problems that arise during the product warranty period will be responded to by the after-sales department within 24

hours, and any resulting costs will be borne by Yongda; Our factory provides lifelong technical service support.
3. Due to natural disasters, human damage, and malfunctions encountered outside the warranty period, our after-sales department will still respond within 24 hours and provide corresponding technical consultation and support to help customers solve problems as soon as possible.



Weifang Yongda FRP Co., Ltd.



86 15105367999



wfydfrp@163.com



plasticfrp.com

West side of the road about 3 kilometers north of Wenhe Bridge Toll Station on National Highway 206, Yingqiu Town, Changle County, Weifang City, Shandong Province, China.